

Safety Data Sheet

Section 1 Product and Company Identification

Manufacturer

Blue Star Lubrication Technology[®], LLC 915 N. Plum Grove Road, Suite C Schaumburg, IL 60173
United States of America

Phone: 847-285-1888 Fax: 847-285-1894

Recommended Usage: Lubricating Grease

Other Identifier: Mixture

Emergency Phone Numbers

847-285-1888 Normal Business Hrs. USA & Canada Chemtrec 800-424-9300 International Chemtrec 703-527-3887

Product Name: Blue Star® XP 9900/460 Series

Section 2 Hazards Identification

Classification of the Mixture: Grayish black to black semi-solid. Petroleum odor.

Most Important Hazards: This material is considered moderately hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). May cause skin sensitization with susceptible individuals. May cause eye, skin and respiratory tract irritation. Harmful is swallowed.

Hazard Classification:

Causes eye and skin irritation – Category 2B May cause allergic skin reaction – Category 1B

Signal Word: Warning!

Pictograms:



Precautionary Statements:

Inhalation - Avoid breathing dust/fume/gas/mist/vapors/spray. Keep container tightly closed. Use only with adequate ventilation.

Skin - Avoid contact with skin and clothing. Wash thoroughly after handling.

Eyes - Avoid contact with eyes. Wash thoroughly after handling.

Ingestion – Harmful if swallowed.

Quantity of Ingredients with Unknown Acute Toxicity: 6%

Section 3 Composition Information on Ingredients			
Ingredient	WT %	CAS#	
Zinc alkyldithiophosphate	< 2	proprietary	
Calcium salts of petroleum sulfonic acids	< 2	61789-86-4	



Section 4 First Aid Measures

Eyes: Flush eyes with running water for at least 15 minutes. If redness, burning, blurred vision or irritation persists, transport to nearest medical facility for additional treatment.

Skin: Flush skin with water, wash with soap and water. If irritation occurs, get medical attention. Remove contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

<u>Ingestion</u>: Do NOT induce vomiting and obtain medical attention. Have victim rinse mouth out with water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

<u>Inhalation</u>: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

Section 5 Fire Fighting Measures

Flammable Properties:

Base Oil Flash point: > 240°C (ASTM D92) Flammable limits in air: N/A Auto ignition temperature: N/A

Extinguishing media: CO₂, dry chemical, foam

Special firefighting measure:

Procedures for an oil fire should be utilized. Use self-contained breathing apparatus. Use foam or dry chemical to extinguish fire. Water may be used <u>only</u> to keep surrounding containers cool. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Section 6 Accidental Release Measures

- Eliminate ignition sources and ventilate area.
- Absorb spillage with inert absorbent material.
- Contain spill and keep from entering waterways or sewers.
- Advise EPA/state agency if required.
- Use proper personal protective equipment for clean-up.
- Treat contaminated absorbent same as spilled product.

Section 7 Handling and Storage

Handling and Storage Precautions: Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area.

Work/Hygienic Practices: Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet. Launder contaminated clothing before reuse. Properly dispose of contaminated leather articles such as shoes or belts that cannot be decontaminated. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.

Section 8 Personal Protection/ Exposure Controls

Engineering Controls: Use adequate ventilation to keep vapors and mists of this material below applicable standards. Recommended work place control parameters - based on mineral oil ACGIH TWA 5 mg/m³.

Respiratory Protection: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Skin Protection: Use protective clothing that is chemically resistant to this product. Acceptable materials for gloves and aprons are: neoprene, nitrile rubber or viton.

Eye Protection: Use safety glasses or goggles. Have suitable eye wash water available.

Other/General Protection: For mists and vapors: Air Purifying, organic vapor cartridge, NIOSH approved respirator. Use self-contained breathing apparatus for environments with unknown concentrations or emergency situations.



Section 9 Physical and Chemical Properties

Color: Grayish black to black

Vapor Pressure: N/A

Solubility in Water:

Proportion Pote

Appearance: Semi-solid % Volatile by Volume: N/A Evaporation Rate
Odor: Characteristic Vapor Density (air = 1): N/A (Butyl Acetate = 1):

Boiling Point: N/A **Reactivity in Water:** Non-reactive **Specific Gravity:** 0.9 – 0.95

Section 10 Stability and Reactivity

Stability: Stable Conditions to avoid: Sources of ignition. Incompatibility: Strong oxidizing or reducing agents.

Decomposition Products: Oxides of Carbon and Hydrogen. **Hazardous Polymerization:** Will not occur.

Section 11 Toxicological Information

Likely Routes of Exposure: Inhalation, skin, eyes and ingestion.

Potential Health Effects:

Eye Effects: Irritant. This mixture can cause irritation and redness.

Skin Effects: Irritant. This mixture may cause inflammation, significant irritation and sensitization in susceptible individuals.

Oral Effects: Harmful if swallowed. Gastrointestinal tract irritation, nausea and vomiting if mixture is swallowed.

Inhalation Effects: Harmful if inhaled. May cause respiratory tract irritation.

Chronic Health Effects: No data available to indicate product or components present at greater than 1% are chronic health hazards.

Mutagenicity: Negative

Carcinogenicity: This mixture contains mineral oils which are considered to be severely refined and not considered to be carcinogenic

under IARC. All the oils in this mixture have been demonstrated to contain less than 3% extractables by the IP 346 test.

Reproductive Effects: Negative.

Teratogenicity: Negative.

Sensitization: Potential Skin Sensitizer Category 1B. Calcium salts of petroleum sulfonic acids may cause allergic skin reaction.

Toxicological Data:

ATE oral is > 2,000 mg/kg ATE dermal is > 4,000 mg/kg

ATE inhalation (mist/aerosol) is estimated at 2.17 mg/L/4 hour

Section 12 Ecological Information

Not classified due to inadequate data available on this mixture. Highly recommend avoidance of release to the environment.

Section 13 Disposal Considerations

Avoid release to the environment. Dispose in a safe manner in accordance with national, state and local regulations. Not a RCRA hazardous waste if uncontaminated. If "used" RCRA criteria must be determined. Dispose of container by recycling or if permitted incineration.

Section 14 Transportation Information

Proper Shipping Name: PETROLEUM LUBRICATING GREASE; NOT REGULATED AS A HAZARDOUS MATERIAL FOR

TRANSPORTATION UNDER 49 CFR.

Shipping Class: 55

Dot Identification Number: N/A

Dot Shipping Label: Not regulated by DOT.

TDG Classification: Not controlled under TDG (Canada).

Not soluble

<1



Section 15 Regulatory Information

U.S. Federal Regulatory Information:

SARA 302 Threshold Planning Quantity: N/A SARA 304 Reportable Quantity: N/A

SARA 311 Categories:

Acute Health Effects: Yes
Chronic Health Effects: No
Fire Hazard: No
Sudden Release of Pressure Hazard: No
Reactivity Hazard: No

EPA/TSCA Inventory: The components of this product are listed on the EPA/TSCA inventory of chemicals.

EPA Hazard Classification Code: Not applicable

CERCLA: No chemicals in this product are subject to the reporting requirements of CERCLA.

SARA Title III - Section 313 Supplier Notification: No Chemicals in this product exceed the DE Minimus reporting level

established by SARA Title III, Section 313 and 40 CFR 372.

WHMIS Classification: WHMIS controlled. Class D; Division 2, Subdivision B: otherwise causing toxic effects. Other Regulations: All components of this formulation are listed on the CEPA-DSL (Domestic Substance List)

Section 16 Other Information

NFPA Hazard Rating:

Health:	1	Slight
Flammability:	1	Negligible
Reactivity:	0	Negligible

SDS Dated: 5/26/2015

*Threshold Limit Value/Personal Exposure Limit

N/A = Not ApplicableN/E = Not Established

Disclaimer of Express or Implied Warranties

The information contained herein is based upon data believed to be reliable and reflects our best professional judgment. Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy of completeness of the information contained therein and assume no responsibility regarding the suitability of this information for the user's intended purpose or for the consequence of its use. Each individual should make a determination as to the suitability of the information for his/her particular purpose(s).