

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

## SECTION 1. IDENTIFICATION

Product name : Shell Tellus S2 V 15

Product code : 001D7747

### Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Oil Products US**  
P.O. Box 4427  
Houston TX 77210-4427  
USA

SDS Request : (+1) 877-276-7285  
Customer Service :

### Emergency telephone number

Spill Information : 877-504-9351  
Health Information : 877-242-7400

### Recommended use of the chemical and restrictions on use

Recommended use : Hydraulic oil

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Aspiration hazard : Category 1

### GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : **PHYSICAL HAZARDS:**  
Not classified as a physical hazard under GHS criteria.  
**HEALTH HAZARDS:**  
H304 May be fatal if swallowed and enters airways.  
**ENVIRONMENTAL HAZARDS:**  
Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**  
No precautionary phrases.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON  
CENTER/doctor.  
P331 Do NOT induce vomiting.  
**Storage:**  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste dis-

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

posal plant.

Hazardous components which must be listed on the label:  
Contains Distillates (petroleum), hydrotreated light naphthenic.

### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Highly refined mineral oils and additives.  
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

### Hazardous components

Chemical Name	Synonyms	CAS-No.	Concentration (%)
Distillates (petroleum), hydrotreated light naphthenic	Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	85 - 95

## SECTION 4. FIRST-AID MEASURES

If inhaled : No treatment necessary under normal conditions of use.  
If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.

When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.  
Obtain medical attention even in the absence of apparent wounds.

In case of eye contact : Flush eye with copious quantities of water.  
If persistent irritation occurs, obtain medical attention.

If swallowed : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

- Most important symptoms and effects, both acute and delayed : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Ingestion may result in nausea, vomiting and/or diarrhoea. Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- Immediate medical attention, special treatment : Treat symptomatically. Call a doctor or poison control center for guidance.
- High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : Do not use water in a jet.
- Specific hazards during fire-fighting : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Avoid contact with skin and eyes.
- Environmental precautions : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
- Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
- Additional advice : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

## SECTION 7. HANDLING AND STORAGE

- Technical measures : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Precautions for safe handling : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
- Avoidance of contact : Strong oxidising agents.
- Product Transfer : This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
- Storage**
- Other data : Keep container tightly closed and in a cool, well-ventilated place.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

Use properly labeled and closable containers.

Store at ambient temperature.

Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene.  
Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

## SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhalable fraction))	5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values
		(Mist)	5 mg/m <sup>3</sup>	OSHA_TRANS

### Biological occupational exposure limits

No biological limit allocated.

### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

**Engineering measures** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.  
Appropriate measures include:  
Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

Define procedures for safe handling and maintenance of controls.  
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.  
Drain down system prior to equipment break-in or maintenance.  
Retain drain downs in sealed storage pending disposal or subsequent recycle.  
Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.  
Practice good housekeeping.

## Personal protective equipment

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.  
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.  
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

Hand protection  
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care.  
Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.  
For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

- dependent on the exact composition of the glove material.  
Glove thickness should be typically greater than 0.35 mm  
depending on the glove make and model.
- Eye protection : If material is handled such that it could be splashed into eyes,  
protective eyewear is recommended.
- Skin and body protection : Skin protection is not ordinarily required beyond standard  
work clothes.  
It is good practice to wear chemical resistant gloves.
- Protective measures : Personal protective equipment (PPE) should meet recom-  
mended national standards. Check with PPE suppliers.

## Environmental exposure controls

- General advice : Take appropriate measures to fulfill the requirements of rele-  
vant environmental protection legislation. Avoid contamination  
of the environment by following advice given in Chapter 6. If  
necessary, prevent undissolved material from being dis-  
charged to waste water. Waste water should be treated in a  
municipal or industrial waste water treatment plant before  
discharge to surface water.  
Local guidelines on emission limits for volatile substances  
must be observed for the discharge of exhaust air containing  
vapour.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Liquid at room temperature.
- Colour : amber
- Odour : Slight hydrocarbon
- Odour Threshold : Data not available
- pH : Not applicable
- pour point : -42 °C / -44 °F Method: ISO 3016
- Initial boiling point and boiling range : > 280 °C / 536 °F estimated value(s)
- Flash point : 170 °C / 338 °F  
Method: ISO 2592
- Evaporation rate : Data not available
- Flammability (solid, gas) : Data not available
- Upper explosion limit : Typical 10 %(V)
- Lower explosion limit : Typical 1 %(V)
- Vapour pressure : < 0.5 Pa (20 °C / 68 °F)

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

	estimated value(s)
Relative vapour density	: > 1 estimated value(s)
Relative density	: 0.872 (15 °C / 59 °F)
Density	: 872 kg/m <sup>3</sup> (15.0 °C / 59.0 °F) Method: ISO 12185
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n-octanol/water	: Pow: > 6 (based on information on similar products)
Auto-ignition temperature	: > 320 °C / 608 °F
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: 350 mm <sup>2</sup> /s (-20 °C / -4 °F) Method: ASTM D445
	15 mm <sup>2</sup> /s (40.0 °C / 104.0 °F) Method: ASTM D445
	3.8 mm <sup>2</sup> /s (100 °C / 212 °F) Method: ASTM D445
Conductivity	: This material is not expected to be a static accumulator.
Decomposition temperature	: Data not available

---

## SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage.



# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

## SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

### Acute toxicity

#### Product:

Acute oral toxicity : LD50 (rat): > 5,000 mg/kg  
Remarks: Expected to be of low toxicity:

Remarks: Aspiration into the lungs may cause chemical pneumonitis which can be fatal.

Acute inhalation toxicity : Remarks: Not considered to be an inhalation hazard under normal conditions of use.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Expected to be of low toxicity:

### Skin corrosion/irritation

#### Product:

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

### Serious eye damage/eye irritation

#### Product:

Remarks: Expected to be slightly irritating.

### Respiratory or skin sensitisation

#### Product:

Remarks: Not expected to be a skin sensitiser.

### Germ cell mutagenicity

#### Product:

: Remarks: Not considered a mutagenic hazard.

### Carcinogenicity

#### Product:

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

<b>IARC</b>	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
<b>ACGIH</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
<b>NTP</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## Reproductive toxicity

### Product:

:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

## STOT - single exposure

### Product:

Remarks: Not expected to be a hazard.

## STOT - repeated exposure

### Product:

Remarks: Not expected to be a hazard.

## Aspiration toxicity

### Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## Further information

### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

## SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically for this product.  
Information given is based on a knowledge of the components and the ecotoxicology of similar products.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). (LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

### Ecotoxicity

#### Product:

Toxicity to fish (Acute toxicity) : Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to algae (Acute toxicity) : Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

Toxicity to bacteria (Acute toxicity) : Remarks: Data not available

### Persistence and degradability

#### Product:

Biodegradability : Remarks: Expected to be not readily biodegradable.  
Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: Contains components with the potential to bioac-

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

cumulate.

## Mobility in soil

### Product:

Mobility

: Remarks: Liquid under most environmental conditions.  
If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

## Other adverse effects

no data available

### Product:

Additional ecological information

: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

Poorly soluble mixture.  
May cause physical fouling of aquatic organisms.

Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues

: Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses

Contaminated packaging

: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation  
Remarks

: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

## SECTION 14. TRANSPORT INFORMATION

### National Regulations

#### US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

### International Regulation

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable  
Ship type : Not applicable  
Product name : Not applicable  
Special precautions : Not applicable

### Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

Additional Information : MARPOL Annex 1 rules apply for bulk shipments by sea.

## SECTION 15. REGULATORY INFORMATION

OSHA Hazards : Aspiration hazard

### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methyl methacrylate	80-62-6	1000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### CERCLA Reportable Quantity

Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA., The components with RQs are given for information.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Immediate (Acute) Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

methyl methacrylate	80-62-6	0.065 %
---------------------	---------	---------

## Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
methyl methacrylate	80-62-6

## California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## The components of this product are reported in the following inventories:

EINECS : All components listed or polymer exempt.

TSCA : All components listed.

DSL : All components listed.

## SECTION 16. OTHER INFORMATION

### Further information

NFPA Rating (Health, Fire, Reactivity) 1, 1, 0

Due to the conversion of this product to GHS classification and labelling, there has been a significant change to the nature of the information presented in chapter 2.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

Version 3.0

Revision Date: 04/30/2015

Print Date: 05/21/2015

DSL = Canada Domestic Substance List  
EC = European Commission  
EC50 = Effective Concentration fifty  
ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals  
ECHA = European Chemicals Agency  
EINECS = The European Inventory of Existing Commercial Chemical Substances  
EL50 = Effective Loading fifty  
ENCS = Japanese Existing and New Chemical Substances Inventory  
EWC = European Waste Code  
GHS = Globally Harmonised System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association  
IC50 = Inhibitory Concentration fifty  
IL50 = Inhibitory Level fifty  
IMDG = International Maritime Dangerous Goods  
INV = Chinese Chemicals Inventory  
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables  
KECI = Korea Existing Chemicals Inventory  
LC50 = Lethal Concentration fifty  
LD50 = Lethal Dose fifty per cent.  
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading  
LL50 = Lethal Loading fifty  
MARPOL = International Convention for the Prevention of Pollution From Ships  
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level  
OE\_HPVS = Occupational Exposure - High Production Volume  
PBT = Persistent, Bioaccumulative and Toxic  
PICCS = Philippine Inventory of Chemicals and Chemical Substances  
PNEC = Predicted No Effect Concentration  
REACH = Registration Evaluation And Authorisation Of Chemicals  
RID = Regulations Relating to International Carriage of Dangerous Goods by Rail  
SKIN\_DES = Skin Designation  
STEL = Short term exposure limit  
TRA = Targeted Risk Assessment  
TSCA = US Toxic Substances Control Act  
TWA = Time-Weighted Average  
vPvB = very Persistent and very Bioaccumulative

Revision Date : 04/30/2015

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.