



SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

1. IDENTIFICATION

Product identifier

Product name QUARTZ INEO MC3 5W-30

Other means of identification

Product Code(s) 35940

Number LKY
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Motor oil.

Uses advised against Do not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA Inc
1201 Louisiana Street, Suite 1800
Houston, TX 77002
Phone: +1 800 323 3198

Contact Point Technical/ HSEQ

E-mail Address USRMLIN-info@total.com

Emergency telephone number

Company Phone Number +1 (908) 862-9300
Emergency telephone +1 866 928 0789 (24h/24, 7d/7)
+1 215 207 0061 (24h/24, 7d/7)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Version GNAM



SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

Unknown Acute Toxicity

52.6727% of the mixture consists of ingredient(s) of unknown toxicity

Hazards not otherwise classified (HNOC)

None known

Other information

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical Name	CAS-No	Weight %
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	40-<50
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	1-<3

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

** The exact percentage (concentration) of composition has been withheld as a trade secret*

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids.

Skin contact Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse.
High pressure jets may cause skin damage. In this case, the casualty should be sent immediately to hospital.

Inhalation Move to fresh air.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

Most important symptoms/effects, acute and delayed

Skin contact Not classified.

Version GNAM



SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

Eye contact	Not classified.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Other information See Section 12 for additional information.

Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g.

Version GNAM



SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands and face before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.
Materials to Avoid	Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits	Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m ³ , NIOSH (REL) TWA 5 mg/m ³ , STEL 10 mg/m ³ , ACGIH (TLV) TWA 5 mg/m ³ (highly refined).
------------------------	--

Exposure controls

Engineering Measures	Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.
-----------------------------	--

Version GNAM



SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

Individual protection measures, such as personal protective equipment

General Information	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.
Eye/Face Protection	If splashes are likely to occur, wear: Safety glasses with side-shields.
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.
Hand Protection	Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Respiratory protection	None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands and face before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Appearance	limpid
Color	yellow To amber
Physical State @20°C	liquid
Odor	Characteristic
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable	
Melting point/range		Not applicable	
Boiling point/boiling range		No information available	
Flash point	> 200 °C > 392 °F		Cleveland Open Cup (COC) Cleveland Open Cup (COC).
Evaporation rate		No information available	
Flammability Limits in Air		No information available	

Version GNAM



SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

upper		No information available	
Lower		No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.840 - 0.860	@ 20 °C	ISO 12185
Density	840 - 860 kg/m ³	@ 20 °C	ISO 12185
Water solubility		Insoluble	
Solubility in other solvents		Soluble in many common organic solvents	
logPow		No information available	
Autoignition temperature	> 250 °C > 482 °F		
Decomposition temperature		No information available	
Viscosity, kinematic	69 mm ² /s 11.4 - 12.45 mm ² /s	@ 40 °C @ 100 °C	ISO 3104 ISO 3104
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	No information available		
Other information			
Freezing Point		No information available	

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to Avoid	Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.
Incompatible Materials	Strong oxidizing agents.
Hazardous Decomposition Products	None under normal use. Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Principle Routes of Exposure	Inhalation, Ingestion, Eye contact, Skin contact.
Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Skin contact	Not classified.
Eye contact	Not classified.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Version GNAM



SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Acute toxicity - Product Information****Product Information** Product does not present an acute toxicity hazard based on known or supplied information.

Oral ATEmix (oral)	9701 mg/kg
Dermal ATEmix (dermal)	9494 mg/kg
Inhalation ATEmix (inhalation-dust/mist)	9.7 mg/l

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)

**Sensitization
Carcinogenicity**

Not classified as a sensitizer.

This product is not classified carcinogenic. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

Chemical Name	ACGIH	IARC	NTP	OSHA
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7				-
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8				-

**Mutagenicity
Reproductive toxicity
STOT-single exposure
STOT - repeated exposure
Other adverse effects**

This product is not classified as mutagenic.

This product does not present any known or suspected reproductive hazards.

Not Classified.

Not Classified.

Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

Aspiration Hazard

Not classified.

12. ECOLOGICAL INFORMATION

Version GNAM



SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

Ecotoxicity

Harmful to aquatic life
Harmful to aquatic life with long lasting effects

Acute aquatic toxicity - Product Information

No information available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8	EL50 (72h) > 100 mg/l (Pseudokirchnerella subcapitata - OCDE 201)	LL50 (96h) > 100 mg/L (Oncorhynchus mykiss - OCDE 203)	EL50 (48h) > 10000 mg/L (Daphnia magna - OCDE 202)	

Chronic aquatic toxicity - Product Information

No information available

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8		NOEL (21d) 10 mg/l (Daphnia magna - OCDE 211)	NOEL (14/28d) >1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

Effects on terrestrial organisms No information available.**Persistence and degradability****General Information** No information available.**Bioaccumulative potential****Product Information** No information available.**logPow** No information available**Component Information**

Chemical Name	log Pow

Version GNAM



SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	-
--	---

Mobility

Soil Given its physical and chemical characteristics, the product generally shows low soil mobility

Air Loss by evaporation is limited

Water Insoluble The product spreads on the surface of the water.

Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any

Version GNAM



SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	no
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois
Zinc alkyl dithiophosphate 68649-42-3		X	X	

16. OTHER INFORMATION

NFPA	Health Hazard 0	Flammability 1	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 0	Flammability 1	Physical Hazard 0	Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Version GNAM



SDS # : 35940

QUARTZ INEO MC3 5W-30

Date of the previous version: 2015-10-15

Revision Date: 2016-08-03

Version 2.01

Revision Date: 2016-08-03

Revision Note *** Indicates updated section

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Legend

Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values

PEL - Permissible Exposure Limits

IDHL - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet

Version GNAM