

Material Safety Data Sheet



SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

SUMMIT 5W30 SN HIGH MILEAGE

Product Use: Motor Oil

Product Number(s): 11225203305W30

Company Identification:

RILCO Lubricants & Services

1320 1st Street

Rock Island, IL 61201

United States of America

www.rilcoinc.com

Date: 02/2015

Transportation Emergency Response

CHEMTREC: (800) 424-9300

Health Emergency

RILCO 309-788-5631

SECTION 2: HAZARDS IDENTIFICATION

Emergency Overview

Physical State: Liquid Color: Amber Odor: Mild
May cause transient, mild irritation to the eyes.
Prolonged or repeated exposure may cause mild irritation to the skin.
Spills may create a slipping hazard.

Key: 4=Severe, 3=Serious, 2=Moderate, 1=Slight, 0=Minimal

Hazard Ranking

	HMIS	NFPA
Health	1	1
Fire	1	1
Reactivity	0	0

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	WT % (approx)
Hydrotreated heavy paraffinic distillate	64742-54-7	80 - 90
Proprietary Ingredients	Confidential	10 - 20
Zinc Dialkyl Dithiophosphate	68649-42-3	0.1 - 1.0
Alkoxy sulfolane	Proprietary	0.42

SECTION 4: FIRST AID MEASURES

EYES: Immediately flush eyes with clean, low-pressure water for at least 15 minutes, occasionally lifting the eyelids. Get medical attention if irritation develops or persists.

SKIN: Wash skin thoroughly with plenty of soap and water. Immediately remove contaminated clothing. Launder contaminated clothing before reuse. Discard saturated leather gloves and shoes. If irritation persists, get medical attention.

INGESTION: DO NOT INDUCE VOMITING. If more than a half-cup full of this material is swallowed, give quantities of water and obtain medical attention. Do not give anything by mouth to an unconscious person. If vomiting occurs, lower head below knees to avoid aspiration.

an inhalation problem under the anticipated conditions of use. In case of overexposure, move person to fresh air. If not breathing, administer artificial respiration and oxygen.

NOTE TO PHYSICIAN: Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: 396 - 399°F. (202 - 204°C)

METHOD OF DETERMINATION: COC D92

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, foam or water spray. Water may be effective, but may cause frothing and spattering. Cool tanks and exposed containers with water. Material will float on water.

HAZARDOUS COMBUSTION PRODUCTS: Toxic fumes, gases of vapors may evolve on burning.

FIRE FIGHTING INSTRUCTIONS: For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of combustion products and oxygen deficiencies. If firefighters cannot work upwind to the fire, respiratory protective equipment must be worn.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Ensure your own health and safety before attempting spill control or clean up. Take the proper precautions see Section 1 for Emergency Overview, Section 8 for Personal Protection and Section 13 for Disposal Considerations.

SMALL SPILL: Remove all sources of ignition. Provide adequate ventilation during clean up. Personal protective equipment must be worn (see Person Protection section for recommendations). Absorb spill with an inert material (e.g., dry sand or earth), then place in a chemical waste container. Use caution, material may present a slipping hazard.

LARGE SPILL: Contain spill and prevent it from entering all water bodies, if possible. Safely stop flow of spill. Evacuate non-essential personnel from immediate spill area. Ventilate area if spilled in a confined space or other poorly ventilated areas. In natural environments, get advice from ecologists on clean-up procedures. This material will float on water. Absorbent materials and pads can be used. Maximize product recovery for reuse or recycling. Transfer liquids and solid diking material to separate, suitable containers for recovery or disposal. Comply with all applicable laws. Spills may need to be reported to the National Response Center (800-424-8802).

SECTION 7: HANDLING AND STORAGE

HANDLING: Keep away from heat, sparks and flame. Keep containers closed when not in use. Use appropriate containment to avoid environmental contamination. Ground all handling equipment to prevent sparking. Avoid breathing vapors or mist. Avoid contact with eyes. Avoid prolonged exposure to skin. Hands should be washed thoroughly after handling.

STORAGE: KEEP OUT OF REACH OF CHILDREN! Odorous and toxic fumes may form from decomposition of this material if stored in temperatures in excess of 113 Deg. F (45 Deg. C) for extended periods of time.

STORAGE TEMPERATURE: Ambient

STORAGE PRESSURE: Atmospheric

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

COMPONENT	OSHA		ACGIH	
	TWA	STEL	TWA	STEL
Oil mist, mineral	5 mg/m ³	N/E	5 mg/m ³	10 mg/m ³
Zinc Dialkyl Dithiophosphate	N/E	N/E	N/E	N/E

ENGINEERING CONTROLS: Use adequate ventilation to keep oil mists of this material below applicable guideline(s)/standard(s).

RESPIRATORY PROTECTION: Under normal conditions, a respirator is not required. If exposure exceeds the occupational exposure limits, follow OSHA standards or equivalent and wear proper NIOSH/MSHA-approved respiratory equipment.

SKIN PROTECTION: Use chemical resistant gloves to avoid prolonged or repeated skin contact. Gloves should be replaced if signs of degradation or chemical breakthrough occur. Long sleeve shirt is recommended. When leaving work area, wash hands/exposed skin with soap and water.

EYE PROTECTION: Use splash goggles or face shield. Eye wash water should be available. Hard contact lenses should not be worn.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (TYPICAL)

APPEARANCE:	<u>Amber</u>
FLASH POINT:	<u>396 - 399 Deg. F (202- 204 Deg. C) by COC D92</u>
ODOR:	<u>Mild</u>
SPECIFIC GRAVITY:	<u>0.8607 – 0.8616 at 60 Deg. F.</u>
SOLUBILITY IN WATER:	<u>Negligible</u>
POUR POINT	<u>-44 Deg C</u>
PHYSICAL STATE:	<u>Liquid</u>
VAPOR PRESSURE:	<u>Not Determined</u>
VAPOR DENSITY:	<u>Not Determined</u>
PERCENT VOLATILE:	<u>Negligible</u>
VISCOSITY@ 100 Deg. C:	<u>10.61 centistokes</u>
VISCOSITY @ 40 Deg. C	<u>63.09 centistokes</u>

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY (CONDITIONS TO AVOID): Material is considered stable at room temperature and pressure. Avoid heat, sparks and open flame.

INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Smoke, carbon monoxide, carbon dioxide, aldehydes, and other products of incomplete combustion. Hydrogen sulfide and alkyl mercaptans and sulfides may also be released. Complete combustion will form oxides of the following elements: nitrogen, sulfur, phosphorus and zinc.

POSSIBILITY OF HAZARDOUS REACTION: None

SECTION 11: TOXICOLOGICAL INFORMATION

EYE IRRITATIONS: Mild, transient irritation may occur upon short-term exposure, based on component data.

SKIN IRRITATION: Not expected to be a primary irritant. Mild skin irritation may occur upon short-term exposure, based on component data. Long-term exposure may cause redness, edema, drying and cracking of skin. Persons with pre-existing skin conditions should avoid contact with this material.

RESPIRATORY IRRITATION: No significant adverse health effects are expected to occur under normal conditions of use. However, exposure to petroleum mist at high levels may be irritating to the nose, throat and lungs.

ORAL TOXICITY: No significant adverse health effects are expected to occur upon short-term exposure based on data from components.

DERMAL SENSITIZATION: No Data

CHRONIC TOXICITY: No Data

CARCINOGENICITY: This product is formulated with mineral oils, which are considered to be severely refined and not considered to be carcinogenic under IARC. The IP346 test has not been used to evaluate these oils.

MUTAGENICITY: No Data

TERATOLOGY (BIRTH DEFECT) INFORMATION: No Data

REPRODUCTION INFORMATION: No Data

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: This material contains alkoxy sulfolane which is toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment, based on calculation.

ENVIRONMENTAL FATE INFORMATION: Component data indicates that plants and animals may experience harmful or fatal effects when coated with petroleum products.

SECTION 13: DISPOSAL CONSIDERATIONS

To determine the proper method of disposal, refer to RCRA (40 CFR 261) as well as federal EPA and state and local regulations. Conditions of use may cause this material to become a “Hazardous Waste”, as defined by state or federal laws. Use approved treatment, transporters and disposal sites in compliance with all applicable laws.

EMPTY CONTAINER WARNING: Empty containers contain residue, which may exhibit the hazards of the product. Do not attempt to refill or clean containers since residue is difficult to remove. Use proper bonding and grounding procedures.

SECTION 14: TRANSPORT INFORMATION

DOT Hazard Class: Not Regulated
ICAO/IATA: Not Regulated
IMDG: Not Regulated

SECTION 15: REGULATORY INFORMATION

GLOBAL REGULATORY INFORMATION

INVENTORY

UNITED STATES (TSCA)

Other TSCA

CANADA (DSL)

EUROPEAN UNION (EINECS)

JAPAN (METI)

PHILIPPINES (PICCS)

SOUTH KOREA (KECL)

AUSTRALIA (AICS)

CHINA (IECSC)

STATUS

All ingredients are on the inventory.

None known

Contains an ingredient that may not be on the inventory.

Contains an ingredient that may not be on the inventory.

Contains an ingredient that may not be on the inventory.

Contains an ingredient that may not be on the inventory.

Contains an ingredient that may not be on the inventory.

Contains an ingredient that may not be on the inventory.

Contains an ingredient that may not be on the inventory.

U. S. REGULATORY INFORMATION

SUPERFUND AMMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA), TITLE III:

This product contains less than 1% zinc.

SARA EXTREMELY HAZARDOUS LIST: This product does not contain greater than 1.0% of any chemical on the SARA Extremely Hazardous list.

SARA 311/312

Immediate (Acute) Health Effects	Yes
Delayed (Chronic) Health Effects	No
Fire Hazards	No
Reactivity Hazards	No

COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT

(CERCLA): None known

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 -

PROPOSITION 65: Based on information currently available, this product does not contain any chemical known to the state of California to cause cancer or reproductive toxicity. If this product is reformulated or further processed, further evaluation should be done based upon such reformulation or processing, as well as upon its final composition and use.

SECTION 16: OTHER INFORMATION

DISCLAIMER OF LIABILITY

The information in this MSDS was obtained from sources, which we believe are reliable. ***HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS.*** The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. ***FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT.***

This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Date: 22 June 2011

Revision Date: None

Revision Indicators: None