

CERTIFICATE OF ANALYSIS

ENEOS Corporation
Lubricants Supply Dept.
Procurement Group
MANAGER Kanki Daisuke

Brand : SUBARU HIGH TORQUE CVTF LINEAR
Lot No : CG5E01

Characteristics	Unit	Results	method
Appearance (Visual)		Pass	Visual method
Density 15° C	g/cm ³	0.8537	K2249
Flash Point COC	°C	196	K2265
Kinematic Viscosity 40° C	mm ² /s	32.00	K2283
100° C	mm ² /s	7.106	K2283
VISCOSITY INDEX		195	K2283
Pour Point	°C	-45.0	K2269
Foaming SEQ.2	ml/ml	0/0	K2518
Acid Number	mgKOH/g	1.11	K2501
Base Number (HCL)	mgKOH/g	1.79	K2501
Base Number (HCL04)	mgKOH/g	3.70	K2501
Copper Strip Corrosion 3Hr. at 100° C		1a	K2513
Shear Stability 10KHz, 1Hr, 28μ			ASTM D2603
Rate of Viscosity Loss (@100° C	%	0.73	ASTM D2603
Brookfield Viscosity -30° C	mPa·s	2486	JPI-5S-26
-40° C	mPa·s	10000	JPI-5S-26
Metal Analysis Ca	mass ppm	377	K0116
P	mass ppm	716	K0116
B	mass ppm	228	K0116
Sulfur	mass %	0.25	K2541