

**ENEOS USA Inc.**

[E'-ne-ohs]


20 N. Martingale Rd, Suite 325, Schaumburg, IL 60173

CERTIFICATE OF ANALYSIS

Product Name
Manufacture Date
Lot/Batch Number

ENEOS ECO CVT FLUID
1/7/2026
NL26A017-B

TEST	METHOD	SPECIFICATION	RESULTS	UNITS
Appearance	Visual	Clear	Clear	
Color	Visual	Blue	Blue	
Flash Point COC	ASTM D92	≥180	208	°C
Density °C	ASTM D4052	≥0.8000	0.85	g/cm ³
Kinematic Viscosity 40°C	ASTM D445	≤30.5	28.8	mm ² /s
Kinematic Viscosity 100°C	ASTM D445	≥6.35	6.37	mm ² /s
Viscosity Index	ASTM D2270	≥175	182	
Pour Point	ASTM D97	≤-39	-45	°C
Total Base Number (HClO ₄)	ASTM D 2896	≥2.8	3.3	mgKOH/g
Water Content	ASTM D6304	≤600	73	mass ppm
Elemental Analysis - Ca	ASTM D4951	0.033 - 0.048	0.041	mass%
Elemental Analysis - P	ASTM D4951	0.050 - 0.070	0.064	mass%
Elemental Analysis - S	ASTM D4951	0.200 - 0.300	0.275	mass%
Foaming SEQ II	ASTM D4951	≤50 / 0	10 / 0	mL/mL


Joy Rogers
Quality Control Manager

FM-QC-233
Rev. 3
05/17/19