

2025/ 9/12

ENEOS Corporation
Lubricants Supply Dept.
Procurement Group
MANAGER Kanki Daisuke

CERTIFICATE OF ANALYSIS

CVTF-LV

Brand : FCL-525ST
Lot No : WP5G01

REC 28 DUMS

Characteristics	Unit	Results	method
Appearance (Visual)		Pass	Visual method
Density 15°C	g/cm ³	0.8387	K2249
Flash Point COC	°C	196	K2265
Kinematic Viscosity 40°C	mm ² /s	25.26	K2283
100°C	mm ² /s	6.375	K2283
VISCOSITY INDEX		222	K2283
Pour Point *1	°C	-47.5	K2269
Foaming SEQ.2	ml/ml	0/0	K2518
Acid Number	mgKOH/g	1.12	K2501
Base Number (HCL)	mgKOH/g	1.60	K2501
Copper Strip Corrosion 3Hr. at 100°C		1	K2513
Brookfield Viscosity -30°C *1	mPa·s	1320	JPI-5S-26
-40°C	mPa·s	3950	JPI-5S-26
Nitrogen Content	mass %	0.19	K2609
Color ASTM		L1.5	K2580
Foaming, SEQ.1	ml/ml	0/0	K2518
SEQ.3	ml/ml	0/0	K2518
Metal Analysis Ca	mass %	0.03	K0116
P	mass %	0.07	K0116
B	mass %	0.02	K0116
S	mass %	0.21	K0116
Shear Stability 10KHz, 1Hr, 28μ			JASO M347

Characteristics	Unit	Results	method
Rate of Viscosity Loss (@100°C) *1	%	4	JASO M347
Only for FUEL OIL and ASPHALT: Multiple base materials are sometimes blended, in which case lot testing may be conducted with samples blended using base materials. *1: This property is measured at regular intervals, and the most recent measured value is shown here. Note : IV NO. USA-KJ-1525 Lubricants Supply Dept. Procurement Group 1-2 Otemachi 1-chome Chiyoda-ku Tokyo 100-8162 Japan NASU AKANE T E L +81-3-6260-2009 F A X +81-3-6260-2096			