



ENEOS USA Inc.
[ENEOS-USA]

20 N. Martingale Rd, Suite 325, Schaumburg, IL 60173

CERTIFICATE OF ANALYSIS

Product Name **ATF SP-4(M)**
Manufacture Date **6/25/2026**
Lot/Batch Number **NL26F088**

TEST	METHOD	SPECIFICATION	RESULTS	UNITS
Density, 15°C	ASTM D4052	Report	0.844	g/cm ³
Color	Visual	Red	Red	
Flash Point	ASTM D92	≥175	210	°C
Kinematic Viscosity, 40°C	ASTM D445	20 - 24	23	mm ² /s
Kinematic Viscosity, 100°C	ASTM D445	5.3 - 5.5	5.4	mm ² /s
Viscosity Index	ASTM D2270	≥150	174	
Total Acid Number	ASTM D664	Report	1.47	mgKOH/g
Total Base Number (HClO4)	ASTM D2896	Report	5.26	mgKOH/g
Aniline Point	ASTM D611	≥95	107.95	°C
Water Content (KF)	ASTM D6304	≤0.10	0.007	mass%
Foaming SEQ I	ASTM D892	≤30 / 0	0 / 0	ml/ml
Foaming SEQ II	ASTM D892	≤30 / 0	0 / 0	ml/ml
Foaming SEQ III	ASTM D892	≤30 / 0	0 / 0	ml/ml
Elemental Analysis - B	ASTM D4951	Report	81	ppm
Elemental Analysis - Ba	ASTM D4951	Report	<0.001	mass%
Elemental Analysis - Ca	ASTM D4951	Report	210	ppm
Elemental Analysis - Mg	ASTM D4951	Report	<0.001	mass%
Elemental Analysis - P	ASTM D4951	Report	320	ppm
Elemental Analysis - S	ASTM D4951	Report	0.25	mass%
Elemental Analysis - Zn	ASTM D4951	Report	<0.001	mass%
Brookfield Viscosity, -40°C	ASTM D2983	≤10000	7,437	mPa·s

Joy Rogers
Quality Control Manager

FM-QC-197
Rev. 1
03/03/20