

CERTIFICATE OF ANALYSIS



ENEOS

Product Name **Suzuki Ecstar Marine FCW Semi Synthetic 10W40**
 Lot Number **NL26G024**
 Date of Manufacture **7/9/2026**

TEST ITEM	METHOD	SPECIFICATION		RESULTS	UNITS
		MIN	MAX		
Appearance	Visual	C & B	--	C & B	--
Color (ASTM)	ASTM D1500	Report	--	L2.5	--
Density 15°C	ASTM D4052	Report	--	0.8656	g/cm3
Flash Point (COC)	ASTM D92	200	--	226	°C
Kinematic Viscosity, 40°C	ASTM D445	Report	--	101.6	cSt
Kinematic Viscosity, 100°C	ASTM D445	12.5	15.5	14.91	cSt
Viscosity Index	ASTM D2270	Report	--	152	--
CCS Viscosity, -25°C	ASTM D5293	--	7000	5906	mPa·s
TAN	ASTM D664	Report	--	2.26	mgKOH/g
TBN (HClO4)	ASTM D2896	Report	--	7.53	mgKOH/g
Pour Point	ASTM D5950	--	-20	-39	°C
Foaming Tendency Seq. I	ASTM D892 IP 146	--	10	0	ml
Foaming Stability Seq. I	ASTM D892 IP 146	--	0	0	ml
Foaming Tendency Seq. II	ASTM D892 IP 146	--	50	0	ml
Foaming Stability Seq. II	ASTM D892 IP 146	--	0	0	ml
Foaming Tendency Seq. III	ASTM D892 IP 146	--	10	0	ml
Foaming Stability Seq. III	ASTM D892 IP 146	--	0	0	ml
NOACK - 250°C, 1 Hr	ASTM D5800	Report	--	11	mass%
Elemental Analysis - B	ASTM D4951	Report	--	0.021	mass%
Elemental Analysis - Ca	ASTM D4951	Report	--	0.222	mass%
Elemental Analysis - P	ASTM D4951	Report	--	0.10	mass%
Elemental Analysis - S	ASTM D4951	Report	--	0.32	mass%
Elemental Analysis - Zn	ASTM D4951	Report	--	0.11	mass%
*1 MRV Viscosity, -30°C	ASTM D4684 (A)	--	60000	22,721	mPa · s
*2 Elemental Analysis - N	ASTM D4629	Report	--	0.06	mass%
*2 TBS Viscosity, 150°C	ASTM D4683	3.5	--	3.9	mPa · s

Notes

- *1 This property is measured at 3 month intervals, and the most recent measured value is shown here.
 *2 This property is measured at 6 month intervals, and the most recent measured value is shown here.

ENEOS USA Inc.

(E'-ne-ohs)

20 N. Martingale Rd, Suite 325, Schaumburg, IL 60173

Joy Rogers, General Manager Quality Control