

CERTIFICATE OF ANALYSIS

**ENEOS**Product Name **ENEOS ECO ATF OE+**Lot Number **NL26E055**Date of Manufacture **5/15/2026**

TEST ITEM	METHOD	SPECIFICATION		RESULTS	UNITS
		MIN	MAX		
Appearance	Visual	Clear	Clear	Clear	--
Color	Visual	Red	Red	Red	--
Density 15°C	ASTM D4052	Report	--	0.8453	g/cm3
Kinematic Viscosity, 40°C	ASTM D445	Report	--	29.42	mm2/s
Kinematic Viscosity, 100°C	ASTM D445	--	6.200	6.13	mm2/s
Viscosity Index	ASTM D2270	150	--	163	--
Foaming Tendency Seq. II	ASTM D892 IP 146	--	50	0	ml
Foaming Stability Seq. II	ASTM D892 IP 146	--	0	0	ml
Elemental Analysis - B	ASTM D4951	0.0100	0.0250	0.0174	mass%
Elemental Analysis - Ca	ASTM D4951	0.0125	0.0275	0.0198	mass%
Elemental Analysis - P	ASTM D4951	0.0350	0.0550	0.0465	mass%
Elemental Analysis - S	ASTM D4951	Report	--	0.0550	mass%
*1 Brookfield, (-40°C)	ASTM D2983	--	12,000	11,012	mPa • s
*1 Pour Point	ASTM D5950	--	-39	-51	°C
*2 Flash Point (COC)	ASTM D92	200	--	202	°C

Notes

*1 This property is measured at 6 month intervals, and the most recent measured value is shown here.

*2 This property is measured at 12 month intervals, and the most recent measured value is shown here.

ENEOS USA Inc.

[E-ne-ohs]

20 N. Martingale Rd, Suite 325, Schaumburg, IL 60173

Joy Rogers, General Manager Quality Control