

CERTIFICATE OF ANALYSIS



ENEOS

Product Name **SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40**
 Lot Number **NL26H029**
 Date of Manufacture **8/11/2026**

TEST ITEM	METHOD	SPECIFICATION		RESULTS	UNITS
		MIN	MAX		
Appearance	Visual	B & C	--	B & C	--
Color (ASTM)	ASTM D1500	Report	--	L2.5	--
Density 15°C	ASTM D4052	Report	--	0.8691	g/cm3
Kinematic Viscosity, 40°C	ASTM D445	Report	--	98.20	mm2/s
Kinematic Viscosity, 100°C	ASTM D445	12.5	15.5	14.09	mm2/s
Viscosity Index	ASTM D2270	Report	--	147	--
CCS Viscosity, -25°C	ASTM D5293	--	7,000	6,998	mPa·s
Pour Point	ASTM D5950	--	-20	-42	°C
Foaming Tendency Seq. I	ASTM D832 IP 146	--	10	0	ml
Foaming Stability Seq. I	ASTM D832 IP 146	--	0	0	ml
Foaming Tendency Seq. II	ASTM D832 IP 146	--	50	0	ml
Foaming Stability Seq. II	ASTM D832 IP 146	--	0	0	ml
Foaming Tendency Seq. III	ASTM D832 IP 146	--	10	0	ml
Foaming Stability Seq. III	ASTM D832 IP 146	--	0	0	ml
Elemental Analysis - B	ASTM D4951	Report	--	0.0056	mass%
Elemental Analysis - Ca	ASTM D4951	Report	--	0.177	mass%
Elemental Analysis - P	ASTM D4951	Report	--	0.0896	mass%
Elemental Analysis - S	ASTM D4951	Report	--	0.257	mass%
Elemental Analysis - Zn	ASTM D4951	Report	--	0.101	mass%
Elemental Analysis - N	ASTM D4629	Report	--	0.0678	mass%
*1 Flash Point (COC)	ASTM D92	200.000	--	226	°C
*1 TAN	ASTM D664	Report	--	2.5	mgKOH/g
*1 TBN (HClO4)	ASTM D2896	Report	--	6.57	mgKOH/g
*2 MRV Viscosity, -30°C	ASTM D4684 (A)	--	60,000	28,840	mPa · s
*2 MRV Yield Stress	ASTM D4684 (A)	--	--	y ≤ 35	Pa
*2 NOACK - 250°C, 1 Hr	ASTM D5800	Report	--	10.8	mass%
*2 TBS Viscosity, 150°C	ASTM D4683	3.5	--	3.85	mPa · s

Notes
 *1 This property is measured at 3 month intervals, and the most recent measured value is shown here.
 *2 This property is measured at 6 month intervals, and the most recent measured value is shown here.

ENEOS USA Inc.

[E-ne-ohs]

20 N. Martingale Rd, Suite 325, Schaumburg, IL 60173

Joy Rogers, General Manager Quality Control