XfR 45856

CERTIFICATE OF ANALYSIS

ENEOS

Product Name SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40
Lot Number NL26K047
Date of Manufacture 10/14/2026

TEST ITEM	METHOD	SPECIFICATION MIN	SPECIFICATION MAX	RESULTS	UNITS
Appearance	Visual	B & C	--	B & C	--
Color (ASTM)	ASTM D1500	Report	--	L2.5	--
Density 15°C	ASTM D4052	Report	--	0.869	g/cm3
Kinematic Viscosity, 40°C	ASTM D445	Report	--	90.15	mm2/s
Kinematic Viscosity, 100°C	ASTM D445	12.5	15.5	13.12	mm2/s
Viscosity Index	ASTM D2270	Report	--	145	--
CCS Viscosity, -25°C	ASTM D5293	--	7,000	6,986	mPa·s
Pour Point	ASTM D5950	--	-20	-42	°C
Foaming Tendency Seq. I	ASTM D892 IP 146	--	10	0	ml
Foaming Stability Seq. I	ASTM D892 IP 146	--	0	0	ml
Foaming Tendency Seq. II	ASTM D892 IP 146	--	50	10	ml
Foaming Stability Seq. II	ASTM D892 IP 146	--	0	0	ml
Foaming Tendency Seq. III	ASTM D892 IP 146	--	10	0	ml
Foaming Stability Seq. III	ASTM D892 IP 146	--	0	0	ml
Elemental Analysis - B	ASTM D4951	Report	--	0.00650	mass%
Elemental Analysis - Ca	ASTM D4951	Report	--	0.196	mass%
Elemental Analysis - P	ASTM D4951	Report	--	0.1012	mass%
Elemental Analysis - S	ASTM D4951	Report	--	0.304	mass%
Elemental Analysis - Zn	ASTM D4951	Report	--	0.1134	mass%
Elemental Analysis - N	ASTM D4629	Report	--	0.071	mass%
*1 Flash Point (COC)	ASTM D92	200	--	224	°C
*1 TAN	ASTM D664	Report	--	2.5	mgKOH/g
*1 TBN (HClO4)	ASTM D2896	Report	--	6.1	mgKOH/g
*2 MRV Viscosity, -30°C	ASTM D4684 (A)	--	60,000	27,859	mPa · s
*2 MRV Yield Stress	ASTM D4684 (A)	--	--	y ≤ 35	Pa
*2 NOACK - 250°C, 1 Hr	ASTM D5800	Report	--	11.5	mass%
*2 TBS Viscosity, 150°C	ASTM D4683	3.5	--	3.82	mPa · s

91.105
1°Δ

Notes
*1 This property is measured at 3 month intervals, and the most recent measured value is shown here.
*2 This property is measured at 6 month intervals, and the most recent measured value is shown here.

ENEOS USA Inc.
[E-ne-ohs]
20 N. Martingale Rd, Suite 325, Schaumburg, IL 60173

Joy Rogers

Joy Rogers, General Manager Quality Control